

5. 承载能力

公称传动比 i		48.57 51.71	40.17 39.23	31.50 30.60	23.34 22.78	20.49 19.75	15.75 15.35	12.64 12.03	10.35 9.75	8.23 8.04
转数/分 连续工作时间率 %		ZQ250、ZQH25 许用输入功率 Pp kw								
1000	40	1.4	1.8	2.0	2.6	3.0	3.4	4.1	4.6	5.0
	100	0.55	0.65	0.9	1.2	1.4	2.0	2.4	3.0	3.75
1500	40	1.8	2.1	2.3	3.1	3.7	4.1	4.7	5.2	5.7
	100	0.8	0.95	1.35	1.8	2.0	3.0	3.8	4.5	5.6
		ZQ350、ZQH35 许用输入功率 Pp kw								
1000	40	3.5	4	5.5	7.1	7.8	10.3	11.9	13.3	15.8
	100	1.25	1.5	2	2.7	3.1	4.6	5.7	7	8.7
1500	40	4.9	5.8	7.9	9.6	11	13.4	15.5	17.8	20.2
	100	1.9	2.3	3	4.1	4.6	6.9	8.5	9.5	13.1
		ZQ400、ZQH40 许用输入功率 Pp kw								
1000	40	4.3	5.9	6.7	9.0	9.5	11.4	13.8	15.6	17.3
	100	2.5	3	4.1	5.6	6.4	8.5	11.1	1.35	16
1500	40	5.9	7.3	8	11	12.5	13.9	16.1	18.7	22
	100	2.7	4.0	6.2	8.5	9.7	12.7	15.8	17.4	19.2
		ZQ500、ZQH50 许用输入功率 Pp kw								
1000	40	10.8	13.4	15.4	20.5	23	26	32	35.5	39
	100	4.3	5.2	7.2	9.7	11	15.4	19.2	23.5	26.8
1500	40	13.9	17	19.2	27	29	32	37	40.5	44.5
	100	6.4	7.8	10.8	14.6	16.6	23	26	32.5	40
转数/分 连续工作时间率 %		ZQ650、ZQH65 许用输入功率 Pp kw								
1000	40	21	26.5	30	40.5	47	51	62.5	70	76
	100	10.1	12.3	17	23	26.5	37	46	50.5	64
1500	40	27	33	36	51	60	63	71	79	96.3
	100	15.2	18.4	25.5	34.5	39.5	50.5	63	70	86
		ZQ750、ZQH75 许用输入功率 Pp kw								
1000	40	37	46	53	72	80	90	110	124	134
	100	14.5	17.5	23.8	35	37.5	52	59	72	90
1500	40	48	59	63	89	100	111	127		
	100	21.5	26.5	36.5	49	56	71	88		
		ZQ850、ZQH85 许用输入功率 Pp kw								
1000	40	54	64	85	110	120	143	174	199	
	100	21.3	24	33	45	51	72	82	99	
1500	40	76	90	101	138					
	100	29.6	35.5	50	68					
		ZQ1000、ZQH100 许用输入功率 Pp Kw								
1000	40	88	108	126	173	188	215			
	100	34.5	41.5	58	78	89	113			
1500	40	112	138	149	209					
	100	51.5	62	87	106					