









装配型式 代号	装 配 型 式	装配型式 代号	装 配 型 式	装配型式 代号	装 配 型 式
1		2		3	
4		5		6	
7		8		9	

4、公称传动比

公称 传动比	ZQ	48.57	40.17	31.5	23.34	20.49	15.75	12.64	10.35	8.23
	ZQH	51.71	39.23	30.60	22.78	19.75	15.35	12.03	9.75	8.04

5. 承载能力

公称传动比 i		48.57	40.17	31.50	23.34	20.49	15.75	12.64	10.35	8.23
		51.71	39.23	30.60	22.78	19.75	15.35	12.03	9.75	8.04
转数/分 连续工作时间率 %		ZQ250、ZQH25 许用输入功率 P _p kw								
1000	40	1.4	1.8	2.0	2.6	3.0	3.4	4.1	4.6	5.0
	100	0.55	0.65	0.9	1.2	1.4	2.0	2.4	3.0	3.75
1500	40	1.8	2.1	2.3	3.1	3.7	4.1	4.7	5.2	5.7
	100	0.8	0.95	1.35	1.8	2.0	3.0	3.8	4.5	5.6
		ZQ350、ZQH35 许用输入功率 P _p kw								
1000	40	3.5	4	5.5	7.1	7.8	10.3	11.9	13.3	15.8
	100	1.25	1.5	2	2.7	3.1	4.6	5.7	7	8.7
1500	40	4.9	5.8	7.9	9.6	11	13.4	15.5	17.8	20.2
	100	1.9	2.3	3	4.1	4.6	6.9	8.5	9.5	13.1
		ZQ400、ZQH40 许用输入功率 P _p kw								
1000	40	4.3	5.9	6.7	9.0	9.5	11.4	13.8	15.6	17.3
	100	2.5	3	4.1	5.6	6.4	8.5	11.1	1.35	16
1500	40	5.9	7.3	8	11	12.5	13.9	16.1	18.7	22
	100	2.7	4.0	6.2	8.5	9.7	12.7	15.8	17.4	19.2
		ZQ500、ZQH50 许用输入功率 P _p kw								
1000	40	10.8	13.4	15.4	20.5	23	26	32	35.5	39
	100	4.3	5.2	7.2	9.7	11	15.4	19.2	23.5	26.8
1500	40	13.9	17	19.2	27	29	32	37	40.5	44.5
	100	6.4	7.8	10.8	14.6	16.6	23	26	32.5	40