

公称速比 i	工 作 类 型 输入转数 r/min	型 号										
		ZL25 ZLH	ZL35 ZLH	ZL42.5 ZLH	ZL50 ZLH	ZL60 ZLH	ZL65 ZLH	ZL75 ZLH	ZL85 ZLH	ZL100 ZLH	ZL115 ZLH	ZL130 ZLH
		中型	中型	中型	中型	中型	中型	中型	中型	中型	中型	中型
7.1	1000	7.92	21.4	40.7	60.0	111	114	192	316	471	654	875
	1500	10.4	28.5	52.7	77.2	146	158	263				
8	1000	7.92	18.8	36.5	60.0	98.4	114	192	280	471	654	875
	1500	10.4	24.7	47.5	77.2	127	158	263				
9	1000	7.17	17.7	34.3	54.5	92.7	104	175	264	431	600	830
	1500	9.47	22.8	44.0	70.4	118	145	241	333			
10	1000	6.46	16.7	32.3	49.3	87.5	94.0	159	247	361	547	733
	1500	8.54	21.1	40.7	63.8	110	121	220	310	487		
11.2	1000	5.75	15.7	29.8	44.0	82.4	84.2	142	222	324	493	662
	1500	7.62	19.6	37.8	57.2	102	108	198	290	441		
12.5	1000	5.06	14.7	26.3	38.9	74.4	126	197	228	403	591	
	1500	6.72	18.3	34.4	50.7	95.9	96.2	162	272	395	547	
14	1000	5.06	12.9	25.0	38.9	68.0	74.4	126	195	288	403	591
	1500	6.72	16.1	31.2	50.7	89.4	96.2	162	241	395	547	
16	1000	4.41	11.8	22.9	34.0	62.3	65.2	111	173	253	355	479
	1500	5.86	15.1	29.3	44.4	79.2	84.5	142	227	349	485	649
18	1000	3.8	10.5	19.9	29.5	55.5	56.6	96.3	150	221	310	419
	1500	5.08	14.1	26.2	38.7	73.7	73.7	124	193	307	427	572
20	1000	3.28	9.34	17.2	25.4	48.9	48.9	83.3	130	192	269	364
	1500	4.38	13.2	22.7	33.5	63.9	63.9	108	168	246	373	501
22.4	1000	3.28	8.00	15.6	25.4	42.5	48.9	83.3	123	192	269	364
	1500	4.38	11.7	22.7	33.5	62.0	63.9	108	168	246	373	501
25	1000	2.85	7.21	14.0	22.2	38.3	42.7	72.8	111	168	236	320
	1500	3.81	10.8	19.8	29.2	56.0	56.0	94.8	148	216	302	443
28	1000	2.38	6.46	12.5	18.5	34.3	35.7	60.9	95.6	141	198	269
	1500	3.18	9.62	16.6	24.5	46.9	46.9	79.6	124	182	255	344
31.5	1000	2.01	5.37	10.6	15.7	30.3	30.3	51.8	81.3	120	169	229
	1500	2.69	8.56	14.1	20.8	40.0	67.9	106	156	218	295	
35.5	1000	1.95	4.70	9.16	15.7	25.0	30.3	51.8	72.5	120	169	229
	1500	2.69	7.02	13.7	20.8	37.3	40.0	67.9	106	156	218	295
40	1000	1.69	4.17	8.13	13.2	22.2	25.6	43.7	64.5	101	143	194
	1500	2.26	6.24	11.9	17.6	33.1	33.8	57.5	89.9	132	186	251
45	1000	1.47	3.47	6.77	11.7	18.5	25.6	39.2	53.7	92.5	143	194
	1500	2.20	5.19	10.1	17.4	27.6	33.8	57.5	79.9	132	186	251

* 本表仅列出在两种不同输入转数及工作类型的情况下,减速器高速轴的许用功率,其他转数、类型、负荷性质可近似地参考此表。但应注意,当每一循环的工作时间 $t_{\text{工作}} > 20$ 分钟时,应按连续型选用,有尖峰载荷的,要比连续型大 2~3.5 倍。